

Release Notes for Nuke and Hiero 17.0v4

Copyright © 2026 The Foundry Visionmongers Ltd.

Release Date

28 July 2026



Note: As part of addressing a security issue, we have back-ported a fix that is unfortunately not compatible with the legacy OFX versions of Denoise and OFlow. As a result, these plugins have been removed from Nuke 16.1 and 17.0 on all platforms and will no longer be available.

Customers should switch to using the newer GPU accelerated versions of Denoise and OFlow (already available in the Nodes Toolbar and Node Graph Tab menu).

Feature Enhancements

Python

- **ID 613698** - The Python layers() function can now retrieve available layer names

Bug Fixes

3D

- **ID 613514** - PreviewSurface would error when a texture input was connected
- **ID 618363** - Alembic (.abc) files exported with baked transform animations did not display geometry in Hydra when reimported using GeoImport, while ReadGeo worked correctly
- **ID 619908** - Camera3 node did not produce correct results when reading from non-24 fps alembic (.abc) files
- **ID 620278** - GeoExport's bake transform operation for abc files incorrectly created over prims in the layer to export.
- **ID 621914** - GeoExport file type specific knobs did not keep their value when reloading a script.
- **ID 622274** - ABC exporting using GeoExport would result in errors in the terminal.

Exporting

- **ID 618218** - Quick Export introduced an audible pop/click when using the H.264 codec

File Formats

- **ID 323244** - When using DWAA and DWAB formats for exr compression, only the RGBA channels were compressed and not the other embedded channels

Gaussian Splats

- **ID 622490** - SplatRender splats_mask knob pop up scene graph button doesn't work

GroupView

- **ID 617837** - The disable_group_view and show_group_view knobs are ignored on the Group node when reopening a script.

Monitor Out

- **ID 597952** - Changing knobs in the Node Graph in Nuke Studio could cause the monitor out display to flip upside down
- **ID 615612** - Decklink 8K Pro did not work at higher Display Modes(frame rates/resolutions) and Pixel Formats (bit depths)

Node

- **ID 617341** - ModelBuilder geometry and other UI elements were not displayed in the Viewer when there was a src input, and 'Show Source Image' was enabled

Node Graph

- **ID 618776** - A crash no longer occurs when viewing the Dope Sheet with a specific script in Nuke

Timeline

- **ID 613881** - Create comp no longer crashes Nuke when overwriting an existing comp
- **ID 617924** - Soft Effects applied inside single-frame clips do not stretch when the clip is extended past 1 frame

Viewer

- **ID 622502** - Nuke crashes when creating a Viewer node in some Nuke scripts with GodRays nodes

Known Issues

3D

- **ID 582327** - The order of errors displayed in the viewer does not match the order of nodes erroring in the Node Graph

- **ID 595605** - The GeoConstrain node and Lookat pipe can have odd handle behaviour when moving constrained objects
- **ID 599250** - Overlapping items in the 3D viewer can display incorrectly when scrubbing through the timeline, occasionally appearing slightly displaced
- **ID 601279** - Snapping the GeoTransform's pivot to a bounding box sets the handles into the wrong place depending on the prim transform order knob setting
- **ID 602910** - Separate EXR AOV files will not work with GeoPoints
- **ID 602975** - GeoPoints mat input does not use texture coordinates
- **ID 603091** - GeoImport frame range knob doesn't affect animated alembic files
- **ID 603322** - GeoPointsToMesh materials are loading incorrectly
- **ID 603629** - Cone softness and angle handles can be pushed past their intended value limits with expressions causing them to become unresponsive
- **ID 604885** - Projections can disappear from the 3D viewer when a FillShader is connected to another part of the scene
- **ID 605111** - GeoImport scene graph options can be slightly delayed when toggling
- **ID 605314** - Creating a Scene+ only connects the Camera to the ScanlineRender2 node and connects the GeoScene node to the Cameras 'scene' pipe
- **ID 606346** - WireframeShader render results can be incorrectly affected by lights in the scene
- **ID 606537** - When texture wrap mode is set to repeat it is not rendered by ScanlineRender2
- **ID 606740** - The PreviewSurface node is not reflecting material colours
- **ID 606741** - GeoTransform 3D hotkey handles do not take precedence over an open text node
- **ID 607127** - Node graph navigation performance slows down when GeoBindMaterial is connected to a second viewer on MacOS
- **ID 607218** - Popup scene graph for mask inputs can show prims that only exist further down the node graph
- **ID 607366** - GeoImport can display an incorrectly scaled camera locator with certain scenes
- **ID 608104** - GeoMerge isn't updating material binding paths
- **ID 608232** - Geo nodes that generate meshes have authoring knobs

- **ID 608460** - Nuke may slow down briefly when creating or deleting nodes with masks set to All Prims on large stages
- **ID 608549** - Adjusting the GeoCameraTracker point size knob can cause small delays if the viewer is connected to ScanlineRender2
- **ID 608700** - Hydra Viewer premults textures without a premult node
- **ID 608924** - PointsGenerator removing connected Camera from dropdown menu
- **ID 609164** - Swapping the A and B pipes of a GeoMerge with two GeoImport attached doesn't swap around their load rules, causing payload update issues.
- **ID 609223** - GeoImport gives uninformative errors when importing an obj file
- **ID 609316** - Materials stay deactivated in 3D viewer after reactivating materials scope in Viewer scene graph
- **ID 609428** - Meshes have added xform parents after exporting to alembic
- **ID 609561** - Camera Randomly Draws in Different Location While Manipulating Z-Far Knob on DeepCrop Node
- **ID 609604** - The 3D viewer now **retains the selected and active camera** throughout timeline playback, regardless of Deep Node activity.
- **ID 609832** - Scene graph override indicators did not sync between multiple Viewers
- **ID 610038** - Geo vertex/face selection persists after node is deleted
- **ID 610149** - The emissive output of the PreviewShader was inconsistent between Hydra and SLR2
- **ID 610265** - Points input label of GeoPoints node sometimes moves away from input when the changing zoom level of the node graph
- **ID 610766** - MtlXStandardSurface node causes Nuke to briefly hang when updating
- **ID 610817** - Activating and Deactivating prims in GeoImport can lag and increases RAM usage
- **ID 610818** - Activating and Deactivating prims in GeoImport can cause GL errors and crash Nuke if the asset being loaded exceeds the RAM available on a machine
- **ID 611614** - The Wireframe shaders operations for over and modulate display the same
- **ID 611771** - Clearing cache frame holds ScanlineRender2 output if it has specific animated texture (animated Roto or GridWarp)

- **ID 612087** - DirectLight is not illuminating an asset with BasicSurface material applied in the Hydra Viewer
- **ID 612134** - Basic surface effects grid and light locator colours.
- **ID 612191** - Camera position jumping around when changing Knob on Deep Nodes
- **ID 612633** - When the default GeoPoints node is given the src input of a GeoSphere the node will error
- **ID 612791** - Unloading a payload does not remove the unloaded items from GeoImport scene graph
- **ID 612804** - The "Select all search items" option in the GeoImport Scene Graph doesn't update graph depth
- **ID 612805** - Decreasing Graph Depth expands branches that were collapsed
- **ID 612857** - Cyclical USD import error disappears when nodes are created below the GeoImport or GeoReference nodes
- **ID 613152** - Geometry created with Nukes 3D geometry nodes are not automatically selected in the viewer or scenegraph on creation
- **ID 613214** - 3D Errors don't show in 2D viewer with Scanline Render on script load
- **ID 613263** - Scenegraph controls can become unresponsive after switching viewers
- **ID 613471** - GeoImport error disappears after frame change
- **ID 613472** - Deleting GeoImport node doesn't clear memory immediately.
- **ID 613548** - A primvar can be incorrectly transformed across spaces
- **ID 613586** - Expression links can break when updating knobs on expression linked nodes
- **ID 613661** - Adjusting mesh topology doesn't update the selection outline in 3D viewer
- **ID 613667** - GeoImport Node Added from 3D Toolbar to Scene Branch Causes Corrupted Render
- **ID 613909** - When you have a frame held/time offset Camera connected to GeoScene in the new 3d system, the time node now correctly effects the camera injected into the USD scene.
- **ID 613932** - Automatic keyframes no longer added on the Error Per Frame knob unless explicitly requested by the user

- **ID 613987** - Animated camera locators in the 3D viewer will break when connected to a enabled Framehold node inside a disabled group
- **ID 614085** - Animated projection using Project3DShader will break when a disabled Framehold node is removed. As a workaround, disconnect and reconnect the camera.
- **ID 614219** - EnvironmentLight node errors when added to the Group
- **ID 614261** - 3D Viewer Displays Incorrect RGB Values (Low RGB Produces Bright Output)
- **ID 614388** - GeoActivation Scenegraph 'collapse all' cannot be undone
- **ID 614439** - Using box selections or lasso selections sometimes misses the Geo from the selection
- **ID 614497** - 3D Viewer selection works only for B input of GeoMerge node set to duplicate prims
- **ID 614511** - SLR2 may inconsistently display/render the currently selected texture from a Switch node
- **ID 614624** - Deviating from the Camera position and reselecting the 3D camera will not reframe the shot
- **ID 614669** - Playback Hangs After Disabling and Removing 2D Node Downstream of TimeOffset
- **ID 614696** - The Classic and new camera nodes, matrix field now turn blue to indicate it is expression-driven (consistent with previous versions).
- **ID 614786** - 3D Nodes like GeoInstance and GeoConstrain will bind together when selected in the DAG
- **ID 614896** - Project3DShader fails to compile GLSL Shaders
- **ID 614914** - Materials don't display if they are de/reactivated in Scene Graph
- **ID 614916** - GeoBindMaterial can't be deselected via nodegraph if material selected in scenegraph
- **ID 614930** - Whilst using GSV's in conjunction with lights, some sliders may not update.
- **ID 615013** - GeoActivation affects Camera branched out upstream in the node graph
- **ID 615032** - Animations on 2D nodes may behave incorrectly when connected to AppendClip.
- **ID 615326** - GeoMerge duplicate in place still duplicates whole heirarchy
- **ID 615776** - GeomOp using Op::Description (rather than GeomOp::Description) crashes in non-obvious way
- **ID 617160** - The USDA camera file has a framerate mismatch when viewed with different 3D nodes.

- **ID 618107** - Materials are not bound to the entire asset in some circumstances.
- **ID 618173** - When using a `DeepMerge` node to combine outputs from a `SplatRender` and `ScanlineRender2` (SLR2), the geometry rendered by SLR2 appears in the incorrect location.
- **ID 618780** - USD `expressionVariables` are not evaluated in Nuke.
- **ID 620119** - Live read Camera doesn't reload data after scrubbing outside of frame range
- **ID 620244** - GeoCamera nodes inside LiveGroups load without any errors
- **ID 620290** - In some cases the lighting in the 3D viewport can appear significantly overexposed when compared to the output of `ScanlineRender2`
- **ID 621744** - Lights with `ShadowAPI` attributes do not display correctly in the 3D viewport
- **ID 622295** - Transforming large USD asset can cause Nuke to crash when playing back
- **ID 622380** - Importing a USD file which contains a proxy object results in a lot of errors in command line
- **ID 623626** - Dragging expressions to individual elements of the positional attributes in the camera properties with authoring enabled causes other elements lose their expression

Annotations

- **ID 606420** - Brush strokes do not build up on self-overlap. You must apply multiple strokes to achieve a buildup effect
- **ID 606536** - Horizontal toolbar doesn't scale down well when reducing the horizontal space available for it
- **ID 606589** - Python API allows creating annotations with a negative duration
- **ID 606901** - Colour Picker sample region cannot be moved when annotations are active
- **ID 607584** - Modifying annotation properties using Python API does not update the viewer instantly
- **ID 607590** - Undo functionality is currently not supported for modifications to annotation drawings properties.
- **ID 607946** - Sync Session can crash when Force Update is pushed to different OS's than host
- **ID 607967** - Duplicating a clip creates duplicate annotations in the timeline and panel, causing inconsistent functionality

- **ID 608354** - Strokes generated via Python render one pixel thicker on Windows and Linux
- **ID 608613** - Timeline markers do not update to reflect Annotations panel filter changes until the mouse hovers over the timeline
- **ID 608873** - Annotations drawn on the B buffer remain associated with that buffer after disabling compare modes, making them inaccessible
- **ID 609499** - Annotation filter stays on "Current Clip" when returning to sequence
- **ID 609500** - The "Current Clip" filter in the Annotations panel is inconsistent and may not display all markers
- **ID 609534** - Annotation export renders all tracks despite 'Tracks for Export' selection
- **ID 609541** - Annotation export ignores cut length settings
- **ID 610225** - Creating a new annotation generates two undo steps (one for the item, one for the stroke), requiring the user to undo twice to revert the action.
- **ID 610322** - Shift+drag to scale the brush tool only goes as small as 2 pixels and as large as 2000. You can type in the tool bar to get lower or higher values.
- **ID 610385** - Exporting a Nuke Annotation File takes as long as rendering the annotation's defined duration, even if you drew nothing on the screen.
- **ID 610392** - All Annotation Comments have the 'Edited' label, even if they're fresh
- **ID 610719** - Vanishing Brush over Sync Review degrades in client-side responsiveness as stroke length increases
- **ID 610845** - Annotations created while viewing the B buffer are not visible during the drawing process; switch to the A buffer to view the strokes.
- **ID 611248** - It is possible to change brush settings using python for locked annotations (also possible through python).
- **ID 611255** - It is possible to lock or unlock annotations using python. However, this behaviour doesn't sync over sync review sessions.
- **ID 611302** - Metadata can be set using Python on any comments or note on a clip. However, once metadata is set, it cannot be unset.
- **ID 611335** - (Windows) Text Annotation can shift above its background
- **ID 611591** - Viewer Annotations markers are slow to update when moving the playhead

- **ID 611730** - When making a selection in a comment or note, the panel won't automatically scroll to accommodate text that's off screen
- **ID 612964** - Comments/Notes can trigger viewer playback shortcuts when aggressively typing (J,K,L))
- **ID 613243** - No clip level annotation markers are visible for single frame footage
- **ID 613349** - Annotation Markers do not update correctly for clips that have been cut into different shots when the Current Clip filter is applied
- **ID 613354** - Single frame annotation markers can be dragged outside the Sequence time making it impossible to get back if it reaches negative values
- **ID 613355** - Focus does not stay in Annotations panel after editing comment or note text
- **ID 613601** - Editing an annotation with the PythonAPI, when the Panel is hidden, causes a panel layout issue
- **ID 613613** - Playback will not show annotations if they're too slow to cache
- **ID 613616** - Brush size does not match cursor size when a clip is reformatted to sequence resolution
- **ID 613697** - Clip Annotations are no longer duplicated in the Panel when a clip is split
- **ID 613855** - Undoing annotations during sync review can have a build-up of unwanted annotations for client side
- **ID 613884** - Create Comp no longer puts Annotations on the wrong frame in the Node Graph if the clip is the moved
- **ID 613988** - Sequence Level annotations are not exported if a Clip Level annotation is in the frame
- **ID 614072** - Overwriting a CreateComp re-renders the annotated frames
- **ID 614339** - Annotation markers won't necessarily appear where you'd expect them if there is more than one copy of that clip on the timeline.
- **ID 614341** - Cancelling a comp that has annotations will lead annotation node to an error'd state
- **ID 614380** - Zooming in and out quickly no longer leaves ghost images of the viewer when annotations are enabled
- **ID 614934** - Focus no longer switches away from Annotations panel after closing a comment/note text box
- **ID 616771** - Annotations Toolbar buttons doesn't much behavior with other Toolbars like the Roto

- **ID 616773** - Scaling multiple annotations in the viewer is not intuitive
- **ID 618360** - Text annotations on Locked annotations can be edited
- **ID 618489** - Notes on Locked Annotations can be deleted in the UI, but reappear after the Annotation is unlocked
- **ID 621798** - Select tool does not retain properties from the previously selected annotations tool.

BlinkScript

- **ID 606124** - OpenCL GPU on Windows outputs grey instead of black on CPU/CUDA
- **ID 624068** - The BlinkScript find function and user selection highlights are the same colour

Colorspace

- **ID 613757** - 8-bit and 16-bit default LUT settings are swapped/incorrect with 2.x.x ACES OCIO configs. To workaround this you can manually swap these defaults to their previous values. This can be done via the Preferences or as knob defaults.
- **ID 620185** - With some OCIO configs, knobs on the OCIODisplay node can change unexpectedly when rendering multiple Write nodes.

File Export

- **ID 618130** - Large NotchLC files get stuck rendering the last frame for a very long time

File Formats

- **ID 619032** - Missing YCBCr matrix knob in quick export

File Import

- **ID 622850** - Reading EXRs from Networked locations can take substantially longer than previously

Gaussian Splats

- **ID 610189** - The 3D Grid in the Nuke 3D viewport is always drawn over the top of the Gaussian Splats.
- **ID 611495** - SplatRender output may appear blurry in some circumstances when compared to the 3D viewport rendering.
- **ID 611708** - Splats and transparent geometry don't blend correctly in the viewer. The geometry will hold the splats out.
- **ID 611885** - No error is displayed when attempting to modify a non-existent Attribute with the GeoFieldSet node.
- **ID 612505** - The viewer overlay for Vector Fields doesn't pan when the Viewport Camera pans
- **ID 612563** - Motion blur is incorrect when the Deep Alpha Threshold knob is set to greater than 0
- **ID 612709** - Warnings about OrthogonalizeBasis can appear in the Terminal when importing splats.
- **ID 612954** - Error: Failed verification: ' primInfo ' is printed to the Terminal
- **ID 613216** - High memory usage while changing frames with very large splats that have been transformed.
- **ID 613290** - The value knob in the FieldConstant node will sometimes default to uninitialised variables
- **ID 613627** - Executing FieldVolumeWrite [LABS] crashes Nuke when Voxel size is set to 0.1.
- **ID 614533** - There are differences in how Fog is rendered in the splat render node and the Nuke viewer
- **ID 614898** - FieldTransform uses the old snapping knob
- **ID 615324** - Drag and dropping splat and ply files creates GeoReference instead of GeoImport
- **ID 616420** - Default prim causes only that prim to export
- **ID 620177** - High memory usage while using GeoGrade
- **ID 622771** - Loading very large splats may cause Nuke to lockup and crash depending on the amount of memory available in your system

Graph Scope Variables

- **ID 608572** - Renaming a Regular Group nested in a VariableGroup, won't update in the Variables tab
- **ID 612465** - The 3D System does not work with VariableGroups with multiple differing variable values in the same node graph

Performance

- **ID 617000** - Nuke is slower to read/write exr files to the network on Windows than Linux on the same hardware

Python

- **ID 618777** - A crash occurs when clearing or reopening a script with a Viewer connected to a GeoPython node in Nuke.

Quick Export

- **ID 595516** - Crash after In and Out points range set on empty frames
- **ID 597886** - Crash when annotations track is longer then video track or sequence starts with annotation track
- **ID 598153** - Error messages when rendering h264 with a high framerate are unclear
- **ID 605191** - There can be color differences between Quick and Custom export
- **ID 605194** - Exporting to Apple Prores 444 XQ with default value in Quick Export can produce a cropped output

Shortcuts

- **ID 607974** - Backdrops can not be created within a group node with the shortcut key

Soft Effects/Transitions

- **ID 594295** - Point selection is incorrect when selecting tangent handles
- **ID 594728** - Shape interaction issues on high DPI displays
- **ID 594910** - Trying to view values for shapes in the curve editor/ dope sheet crashes studio
- **ID 594912** - Copying points from one shape to another does not work
- **ID 595195** - Crash when using Python to add a layer with shapes in it to the curveknob
- **ID 595487** - Viewing roto shapes crashes hiero/player
- **ID 595488** - Changing roto knob settings only shows after viewer refresh
- **ID 595677** - Output mask knob works differently to the nodegraph

Timeline

- **ID 608402** - Although the "New Track(s) from EDL/XML/AAF" dialog accepts OTIO files, the specific "New Track from OTIO" option should be used for this format.
- **ID 617107** - The Viewer in Nuke Studio/Hiero can become non-functional after waking from sleep
- **ID 622626** - The clipping warning button stays highlighted when disabled

UI

- **ID 595210** - Typo in Edit Workspace details dialog

Qualified Operating Systems

- macOS Sequoia (15.x), or macOS Tahoe (26.x)
- Note: Nuke 15.0 and later support Apple's silicon hardware.

For more information on Foundry products and supported macOS versions, see Foundry Knowledge Base article [Q100592](#).

- Windows 11 (64-bit)

- Linux Rocky 9.0 (64-bit)

Nuke requires **libnuma** to run under Linux distributions, the library is required by the Nablet H264 Codec SDK.

The currently supported version of VFX Reference Platform includes library versions that are only compatible with Rocky 9.0.

Other operating systems may work, but have not been fully tested.

Requirements for Nuke's GPU Acceleration

If you want to enable Nuke to calculate certain nodes using the GPU, there are some additional requirements. See the Release notes for full details of requirements for GPU acceleration based on your Nuke version.

NVIDIA

Nuke 16.1 requires an NVIDIA GPU with graphics drivers capable of running CUDA 11.8 or above

Nuke 17.0 requires an NVIDIA GPU with graphics drivers capable of running CUDA 12.8 or above

A list of the compute capabilities of NVIDIA GPUs is available at <https://developer.nvidia.com/cuda-gpus>

The compute capability is a property of the GPU hardware and can't be altered by a software update.

On Windows and Linux, CUDA graphics drivers are bundled with the regular drivers for your NVIDIA GPU. Driver versions 522.06 (Windows) and 520.61.05 (Linux), or above are required. See <https://www.nvidia.com/Download/Find.aspx> for more information on compatible drivers.

We recommend using the latest graphics drivers, where possible, regardless of operating system.

AMD

Bitwise equality between GPU and CPU holds in most cases, but for some operations there are limitations to the accuracy possible with this configuration.

- On Windows and Linux, an AMD GPU from the following list:

Other AMD GPUs may work, but have not been fully tested.

- AMD Radeon PRO W7900
- AMD Radeon PRO W6600

- AMD Radeon PRO W6800
- AMD Radeon Pro W5700
- AMD Radeon RX 6800 XT

For information on the recommended driver for each GPU, see <https://www.amd.com/en/support>

Multi-GPU Processing

Nuke's GPU support includes an **Enable multi-GPU support** option. When enabled in the preferences, GPU processing is shared between the available GPUs for extra processing speed.

Multi-GPU processing is only available for identical GPUs in the same machine. For example, two NVIDIA GeForce GTX 1080s or two AMD Radeon™ Pro WX 9100s.

GPU Requirements for the Machine Learning Toolset

Training using the CopyCat node requires an NVIDIA GPU, with compute capability 3.5 or above; or MacOS Apple silicon integrated GPUs.

If an appropriate GPU is not available, Inference and other machine learning plug-ins can run on the CPU with significantly degraded performance.

Apple M Series

Native support for Apple silicon hardware began with Nuke 15.0 and later versions. The following machines has been tested.

- Mac Pro
- Mac Studio
- Mac Mini
- MacBook Pro

WARNING: Although AMD GPUs are enabled on other Mac models, they are not officially supported and are used at your own risk.

Note: For Nuke 14.1 and earlier, Nuke is supported under Rosetta emulation on Apple silicon hardware. For the latest and most detailed information on GPU acceleration requirements for your specific Nuke version, always refer to the official release notes.

Developer Notes

As Nuke develops, we sometimes have to make changes to the API and ABI under the hood. We try to keep these changes to a minimum and only for certain releases, but from time to time API and ABI compatibility is not guaranteed. See the following table for the situations when you may have to recompile your plug-ins and/or make changes to the source code.

Release Type	Example	Compatibility	Recompile	Rewrite
Version	14.0v1 to 14.0v2	API and ABI		
Point	14.0v1 to 14.1v1	API	●	
Major	14.0v1 to 15.0v1	-	●	●

Additionally, node **Class()** names occasionally change between major releases. While these changes do not affect legacy scripts, you may not get the results you were expecting if a node class has been modified. The **toolbars.py** file, used to create Nuke's node toolbar, contains all the current node class names and is located in **<install_directory>/plugins/nukescripts/** for reference.

As an example, between Nuke 13 and Nuke 14, the Axis node **Class()** changed from Axis3 to Axis4. In the **toolbars.py** file for the two releases, the entries for the Axis node appear as follows:

```
m3Dclassic.addCommand(
    "Axis",
    "nuke.createNode(\"Axis3\") ",
    icon="Axis.png",
    tag=MenuItemTag.Classic,
    node="Axis3",
    tagTarget=MenuItemTagTargetFlag.TabMenu)
```

```
m3D.addCommand(
    "Axis",
    "nuke.createNode(\"Axis4\") ",
    icon="Axis_3D.png",
    tag=MenuItemTag.Beta, node="Axis4")
```